

4.3 inch TFT LCD



PROFILE

- Type: IPS TFT/Normal Black
- Display format: 800(RGB)×480
- Controller IC: ST7282 (or equivalent)
- Interface: RGB 24bit
- +3.3V power supply
- Without touch panel

FEATURES

NO.	ITEM	SPECIFICATION	UNIT
1	Panel Size	4.3	inch
2	Outline Dimension	105.5(W) x 67.2(H) x 3.15(T)	mm
3	Viewing Area	96.7 x 55.5	mm
4	Active Area	95.04 x 53.87	mm
5	Number of Pixels	800(H) × 3(RGB) × 480(V)	pixels
6	Pixel Pitch	0.108(W) × 0.108(H)	mm
7	Pixel arrangement	RGB vertical stripe	-
8	Display Mode	Normal Black	-
9	Viewing Direction	All (IPS)	-
10	Display Color	16.7M	-
11	Luminance(cd/m2)	600(TYP.)	nit
12	Contrast Ratio	400(TYP.)	-
13	Surface Treatment	Anti-Glare	-
14	Interface	24bit-RGB	-
15	Backlight	White LED	-
16	Drive IC	ST7282	-
17	Operation Temperature	-20~70	°C
18	Storage Temperature	-30~80	°C

MECHANICAL DATA		
ITEM	STANDARD VALUE	UNIT
Module Dimension	105.5 x 67.2	mm
Viewing Area	96.7 x 55.5	
Active Area	95.04 x 53.87	
Pixel Pitch	0.108 × 0.108	
Height	3.15	

ABSOLUTE MAXIMUM RATINGS					
ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Supply Voltage	VDD	-0.3	3.3	4.0	V
Logical Supply Voltage	VDDIO	1.8	-	3.6	


ELECTRICAL CHARACTERISTICS						
ITEM	SYMBOL	CONDITION	STANDARD VALUE			UNIT
			MIN	TYP	MAX	
Logical Supply Voltage	VDDIO	Ta =25°C	1.8	-	3.6	V
Supply Voltage	VDD		-0.3	3.3	4.0	
LED Forward Voltage	Vf	Ta =25°C	-	15.5	-	V
LED Forward Current	If		-	40	-	mA

For detailed information, please refer to the “Product Numbering System” document.

PIN DESCRIPTION FOR LCD PANEL			
NO.	SYMBOL	I/O	FUNCTION
1	LED(-)	P	Power for LED backlight cathode
2	LED(+)	P	Power for LED backlight anode
3	GND	P	Power ground
4	VCC	P	Power voltage
5	R0	I	Red data (LSB)
6	R1	I	Red data
7	R2	I	Red data
8	R3	I	Red data
9	R4	I	Red data
10	R5	I	Red data
11	R6	I	Red data
12	R7	I	Red data (MSB)
13	G0	I	Green data (LSB)
14	G1	I	Green data
15	G2	I	Green data
16	G3	I	Green data
17	G4	I	Green data
18	G5	I	Green data
19	G6	I	Green data
20	G7	I	Green data (MSB)
21	B0	I	Blue data (LSB)

22	B1	I	Blue data
23	B2	I	Blue data
24	B3	I	Blue data
25	B4	I	Blue data
26	B5	I	Blue data
27	B6	I	Blue data
28	B7	I	Blue data (MSB)
29	GND	P	Power ground
30	DCLK	I	Pixel clock
31	DISP	I	Display on/ off
32	HSYNC	I	Horizontal sync signal
33	VSYNC	I	Vertical sync signal
34	DE	I	Data enable
35	NC	-	No connection
36	GND	P	Power ground
37	X1	I/O	Right electrode - differential analog
38	Y1	I/O	Bottom electrode - differential analog
39	X2	I/O	Left electrode - differential analog
40	Y2	I/O	Top electrode - differential analog

I/O: I: input, O: output, P: power

DIMENSIONS in millimeters

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Display Zone Co., Ltd., its affiliates, agents, and employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheets or in any other disclosure relating to any products.

Display Zone makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Display Zone disclaims:

- (i) any and all liability arising out of the application or use of any product,
- (ii) any and all liability, including without limitation special, consequential or incidental damages,
- (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Display Zone's knowledge of typical requirements that are often placed on Display Zone products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Display Zone's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Display Zone of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Display Zone disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Display Zone products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Display Zone product could result in personal injury or death. Customers using or selling Display Zone products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Display Zone personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Display Zone. Product names and markings noted herein may be trademarks of their respective owners.