


0.96 inch OLED module

**PROFILE**

- Type: Passive graphic
- Display Color: Dual-chrome (Light Blue&Yellow)
- Display format: 128 x 64 dots
- Duty cycle: 1/64
- +3.3V power supply
- Controller IC: SSD1315
- Interface: 3-wire SPI

FEATURES

NO.	ITEM	SPECIFICATION	UNIT
1	Panel Size	0.96	inch
2	Outline Dimension	24.7(W) x 16.6(H) x 1.3(T)	mm
3	Viewing Area	22.74 x 12.2	mm
4	Active Area	21.74 x 11.2	mm
5	Number of Dots	128 × 64	pixels
6	Dot Size	0.15(W) × 0.15(H)	mm
7	Dot Pitch	0.17(W) × 0.175(H)	mm
8	Display Mode	Passive graphic	-
9	Viewing Direction	All	Degree
10	Display Color	Light Blue&Yellow	-
11	Luminance(cd/m ²)	105(TYP.) (Vcc Generated by Internal DC/DC)	cd/m ²
12	Contrast Ratio	2000(TYP. In Dark Room)	-
14	Interface	3-wire SPI	-
16	Drive IC	SSD1315	-
18	Operation Temperature	-40~85	°C
19	Storage Temperature	-40~85	°C

ABSOLUTE MAXIMUM RATINGS				
ITEM	SYMBOL	MIN	MAX	UNIT
Supply Voltage for Logic	V _{DD}	-0.3	4	V
Supply Voltage for Display	V _{CC}	0	16.5	V
Supply Voltage for DC/DC (Internal DC/DC Enable)	V _{BAT}	-0.3	4.5	V
Operating Temperature	T _{OP}	-40	85	°C
Storage Temperature	T _{STG}	-40	85	°C
Life Time (110 cd/m ²)		10,000	-	hour
Life Time (80 cd/m ²)		30,000	-	hour
Life Time (60 cd/m ²)		50,000	-	hour

ELECTRICAL CHARACTERISTICS						
ITEM	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Supply Voltage for Logic	V _{DD}		1.65	2.8	3.3	V
Supply Voltage for Display (Supplied Externally)	V _{CC}	Internal DC/DC Disable	8.5	9.0	9.5	V
Supply Voltage for DC/DC	V _{BAT}	Internal DC/DC Enable	3.5	-	4.2	V
Supply Voltage for Display (Generated by Internal DC/DC)	V _{CC}	Internal DC/DC Enable	7.0	-	7.5	V
High Level Input	V _{IH}	I _{OUT} =100μA, 3.3MHz	0.8xV _{DD}	-	V _{DD}	V
Low Level Input	V _{IL}	I _{OUT} =100μA, 3.3MHz	0	-	0.2xV _{DD}	V
High Level Output	V _{OH}	I _{OUT} =100μA, 3.3MHz	0.9xV _{DD}	-	V _{DD}	V
Low Level Output	V _{OL}	I _{OUT} =100μA, 3.3MHz	0	-	0.1xV _{DD}	V
Operating Current for V _{DD}	I _{DD}		-	160	220	μA
Operating Current for V _{CC} (V _{CC} Supplied Externally)	I _{CC}		-	9	15	mA
Operating Current for V _{BAT} (V _{CC} Generated by Internal DC/DC)	I _{BAT}		-	26.0	32.0	mA
Sleep Mode Current for V _{DD}	I _{DD, SLEEP}		-	-	10	μA
Sleep Mode Current for V _{PP}	I _{CC, SLEEP}		-	-	10	μA





For detailed information, please refer to the “Product Numbering System” document.

PIN DESCRIPTION FOR OLED MODULE			
NO.	SYMBOL	I/O	FUNCTION
1	C2P	I	Positive Terminal of the Flying Inverting Capacitor
2	C2N	I	Negative Terminal of the Flying Boost Capacitor
3	C1P	I	Positive Terminal of the Flying Inverting Capacitor
4	C1N	I	Negative Terminal of the Flying Boost Capacitor
5	V _{BAT}	P	Power Supply for DC/DC Converter Circuit
6	V _{SS}	P	Ground of Logic Circuit
7	V _{DD}	P	Power Supply for Logic
8	CS	I	Chip Select

9	RES	I	Power Reset for Controller and Driver
10	D0	I	Serial Clock Input Signal
11	D1	I/O	Serial Data Input Signal
12	IREF	I	Current Reference for Brightness Adjustment
13	VCOMH	O	Voltage Output High Level for COM Signal
14	Vcc	P	Power Supply for OEL Panel

I/O: I: input, O: output, P: power

DIMENSIONS in millimeters



Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Display Zone Co., Ltd., its affiliates, agents, and employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheets or in any other disclosure relating to any products.

Display Zone makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Display Zone disclaims:

- (i) any and all liability arising out of the application or use of any product,
- (ii) any and all liability, including without limitation special, consequential or incidental damages,
- (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Display Zone's knowledge of typical requirements that are often placed on Display Zone products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Display Zone's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Display Zone of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Display Zone disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Display Zone products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Display Zone product could result in personal injury or death. Customers using or selling Display Zone products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Display Zone personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Display Zone. Product names and markings noted herein may be trademarks of their respective owners.